

# Technical data

## BSTL 350-88.

### BSTL 350-88

Press force		kN	350
Tool loading area	L - R	mm	880
Speed	Min.	spm	100
	Max.	spm	1200
Mains voltage (EN 60204) <sup>A)</sup>		V	400
Mains frequency (EN 60204) <sup>A)</sup>		Hz	50 / 60
Connected load	Max.	kVA	37
Control voltage		VDC	24
Drive power of main motor		kW	15
Compressed air connection R 1/2"	Min.	bar	6
	Max.	bar	10
Fixed stroke - 4 options		mm	15.9
		mm	19
		mm	25.4
		mm	31.8
Ram adjustment		mm	51
Shut height (depending on stroke)	Min.	mm	228.6
	Max.	mm	287.6
Bolster area	L - R	mm	870
	F - B	mm	536
	Height <sup>C)</sup>	mm	1154
Ram area	L - R	mm	776
	F - B	mm	360
Strip inlet height	Min.	mm	80
	Max.	mm	150
Strip inlet width (machine)	Max.	mm	230
Base plate opening	L - R	mm	830
	F - B	mm	180

### DIMENSIONS<sup>D)</sup>

Machine (standard feed unit)	L - R	mm	2290
	F - B	mm	1130
	Height	mm	2820
	Weight (app.)	kg	5700

### FEED UNITS

	Standard	BSV 120 L
--	----------	-----------

