

# Technical data

## BSTA 200.

		BSTA 200 - 60		BSTA 200 - 70	
Press force		kN	200	200	
Tool loading area	L - R	mm	600	700	
Speed	Min.	spm	100	100	
- Adjustable stroke machine (standard) <sup>1)</sup>	Max.	spm	1800	1800	
- Fixed stroke machine <sup>2)</sup>	Max.	spm	2000	2000	
Mains voltage (EN 60204) <sup>A)</sup>		V	400	400	
Mains frequency (EN 60204) <sup>A)</sup>		Hz	50 / 60	50 / 60	
Connected load <sup>B)</sup>	Max.	kVA	29	29	
Control voltage		VDC	24	24	
Drive power of main motor		kW	15	15	
Compressed air connection R 1/2"	Min.	bar	6	6	
	Max.	bar	10	10	
Adjustable stroke (standard)		mm	8 / 13 / 16 / 19 /	8 / 13 / 16 / 19 /	
		mm	25 / 32 / 38	25 / 32 / 38	
Fixed stroke <sup>A)</sup>	Max.	mm	44	44	
Ram adjustment range		mm	40	40	
Shut height <sup>A)</sup> (according to stroke)	Min.	mm	181	181	
	Max.	mm	236	236	
Bolster area	L - R	mm	590	690	
	F - B	mm	426	426	
	Height <sup>C)</sup>	mm	1100	1100	
Ram area	L - R	mm	590	690	
	F - B	mm	270	270	
Strip inlet height <sup>A)</sup>	Min.	mm	50	50	
	Max.	mm	120	120	
Strip inlet width (machine)	Max.	mm	190	190	
Base plate opening	L - R	mm	540	640	
	F - B	mm	160	160	
<b>Dimensions</b>					
Press (standard BBV)	L - R	mm	1700	1790	
- With manual stroke adjustment	F - B	mm	915	915	
	Height	mm	2460	2460	
	Weight (app.)	kg	3300	3500	
<b>Strip feed unit</b>					
	Standard Variations	BBV 180 BSV 75 BSV 170 BZV 61			

<sup>A)</sup> Options on request. <sup>B)</sup> Incl. standard sockets for peripheral equipment. <sup>C)</sup> Above floor level.

<sup>1)</sup> Adjustable stroke machine with 2000 spm available as option. <sup>2)</sup> Fixed stroke machine with 8 mm shut height. Subject to change.